



**NOTES:**

- 1 - CLASS A-4 CONCRETE MINIMUM STRENGTH - 4000 PSI
- 2 - TOLERANCE - CONNECTOR LOCATION +/- 1/16" LENGTH +/- 1/4"
- 3 - CHAMFERS 3/4"
- 4 - WEIGHT - 4800 LBS. OR 400 PLF
- 5 - CONNECTOR PLATE TOLERANCE 1/16" +/- (EXCEPT LENGTH 5-3/4" +)
- 6 - A-36 PLATE
- 7 - ASTM 706 GRADE 60 REBAR
- 8 - A 185 = WELDED WIRE FABRIC FOR CONCRETE
- 9 - REFLECTIVE SHEETING PLATES SHALL BE SPACED AT 10 FEET (SEE LOCATION ON DRAWING MPT 4).

EFFECTIVE DATE: APRIL 1996

COMMONWEALTH OF PUERTO RICO DEPARTMENT OF TRANSPORTATION AND PUBLIC WORKS HIGHWAY AND TRANSPORTATION AUTHORITY		
<b>MAINTENANCE AND PROTECTION OF TRAFFIC</b>	RECOMMENDED BY	<i>[Signature]</i>
	DESIGN AREA DIRECTOR DATE	May 11, 1996
	APPROVED BY:	<i>[Signature]</i>
<b>TEMPORARY CONCRETE BARRIER POSITIVE CONNECTING BARRIER J-J HOOK DESIGN</b>	EXECUTIVE DIRECTOR DATE	
	APPROVED BY:	<i>[Signature]</i>
DIV. ADM. FLWA-PR DIVISION		DATE: 5/10/96
DATE	REVISION	BY
STD. DWG.	MPT	7 OF 22

POSITIVE CONNECTING BARRIER J-J HOOK DESIGN AS MANUFACTURED BY EASI-SET INDUSTRIES, P.O. BOX 300, MIDLAND, VA 22728, (703) 439-8911